



PRODUCT-DETAILS

T4N 250 UL/CSA TMA 200-1000..2000 3p F F

T4N 250 UL/CSA TMA 200-1000..2000 3p F F



General Information	
Extended Product Type	T4N 250 UL/CSA TMA 200-1000..2000 3p F F
Product ID	1SDA057183R1
EAN	8015644585181
Catalog Description	T4N 250 UL/CSA TMA 200-1000..2000 3p F F
Long Description	C.BREAKER TMAX T4N 250 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 200 I3=1000...2000 A
Ordering	
EAN	8015644585181
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Weight	1 kg

Container Information	
Package Level 1 EAN	8015644585181
Additional Information	
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Version	F
Technical	
Mechanical Durability	20000 cycle
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 9.9 W
Rated Current (I _n)	200 A
Rated Operational Voltage	600 V AC 600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(240 V AC) 65 kA (480 V AC) 25 kA (600 V AC) 18 kA (500 V DC) 2 Poles in Series 25 kA (600 V DC) 3 Poles in Series 16 kA
Rated Uninterrupted Current (I _u)	250 A
Release	TMA
Release Type	TM
Short-Circuit Performance Level	N
Standards	UL 489 CSA C22.2
Sub-type	T4
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test})	3500 V
Certificates and Declarations	
Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	1SDL000165R0004
Instructions and Manuals	1SDC210023D0201
Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T



Product image
not available