

60 Amp Non-Fused AC Disconnect Plus GFCI Receptacle

- **Two styles available:** non-fused pullout or non-automatic styles
- 15A duplex GFCI receptacle included (meets latest UL requirements)
- Smart design allows cover to be closed while cords are plugged in to the GFCI receptacle
- Disconnect switch positioned above GFCI receptacle allows easier access
- On pullout model, handle stores inside enclosure in OFF position
- Large, easy-to-read ON/OFF markings
- Cover conveniently stores in up position
- Padlock ring for extra security

- **Meets NEC #210.63 and NEC #406.8(B)(1)**

NEC #210.63 Heating, Air-Conditioning, and Refrigeration Equipment Outlet

A 125-volt, single-phase, 15- or 20-ampere-rated receptacle outlet shall be installed in an accessible location for the servicing of heating, air-conditioning, and refrigeration equipment. The receptacle shall be located on the same level and within 7.5 m (25 ft) of the heating, air-conditioning, and refrigeration equipment. The receptacle outlet shall not be connected to the load side of the equipment disconnecting means.

NEC #406.8 Receptacles in Damp or Wet Locations

(B) Wet Locations

(1) 15- and 20-Ampere Outdoor Receptacles 15- and 20-ampere, 125- and 250-volt receptacles installed outdoors in a wet location shall have an enclosure that is weatherproof whether or not the attachment plug cap is inserted.

- **240V ac, single phase**
- **UL and CUL Listed**
- **NEMA 3R rated enclosure**



Non-fused pullout model
TFN60RGFR



Non-automatic switch model
TNA60RGFR

60 Amp Non-Fused AC Disconnect Plus GFCI Receptacle




- 60 amps, 240V AC, 1 Phase
- Max HP = 10 HP
- Power Outlet: 15A, 120V AC
- Type 3R enclosure
- Enclosure dimensions: 5 3/4" x 7 1/8" x 5 3/16"


Description	Cat. No.	List Price, GO-131A
Non-Automatic Switch	TNA60RGFR	\$325.00
Non-Fused Pullout	TFN60RGFR	\$300.00



The enclosures on these AC disconnects are designed to allow easy access to the disconnect even with a cord or cords plugged into the GFCI outlet and to permit lowering of the cover with cords in place.



Typical Wiring Diagram



Power Outlet

ABB Inc.
305 Gregson Drive
Cary, NC 27511

© Copyright 2019 ABB. All rights reserved
Information provided is subject to change without notice. Please verify all details with ABB. All values are design or typical values when measured under laboratory conditions, and ABB makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.